



S.Korea Origin

HEX-F is a high quality non oxidised, polyethylene wax manufactured by **KPIC**.

Applications

Plastic processing

- Lubricant for PVC pipe & profile
- Carrier material and dispersing aid in pigment and additive concentrations

Printing Inks / Thermoplastic Paint

- Abrasion prevention

Paraffin compounding, candle industry

- Increase of solidification and drop points

Polishes

- In solvent-containing and low solvent applications

Hotmelts

- Viscosity adjustment

Technical Data*			
	Unit	Testing Method	Standard Value
Molecular Weight, Mn	-	GPC	1500 ± 500
Viscosity at 149 °C	Cps	ASTM D3236	18 – 30
Density	g/cc	ASTM D1505	0.95
Penetration	d.mm	ASTM D1321	3
Melting point	°C	ASTM D3954	114 - 120
Type of delivery	-	visual	flakes
Appearance	-	visual	white

Note: Typical values; not to be construed as specifications. User should confirm results by their own test.

*As per Data provided by the exporter.

Amar Jyoti Industries

Office: A - 94/6 Wazirpur Industrial Area, Delhi 110052, India.

Telefax: +91-11-27371557

Web: www.amarjyotiwax.in

Email: amarjyotiindustries@gmail.com